



639.00 EUR  
incl. 19% VAT, plus [shipping](#)

**New from September 2011:**

- New panel type (Higher contrast)
- Metal- instead of plastic-enclosure

The CTF-1210 TFT-Display is equipped with a 12.1" TFT panel and comes with many nice features. In any case it is the ideal display- and input-unit for your Laptop, CarPC or HTPC. Because of the 4:3 aspect ratio and the size of 12.1", the display is perfectly suitable for being used in POS-section or on boats. With the touchscreen functionality you easily can control your PC. The brilliant VGA-display ensures a maximum readability and sharpness.

The CTF-1210 can be used with any PC/MAC with VGA- and USB port.

Driver-CD included, compatible with :

- Windows 95/98/ME/NT4/2000/XP/7/8/8.1/10
- XP Tablet PC Edition
- Windows CE 2.12, 3.0, .net
- Linux RedHat,Mandrake,..
- Macintosh OS 9.x, 10.x
- DOS,..

| <b>Specifications</b>        |   |
|------------------------------|---|
| <i>Display size</i>          | 12.1" digital   |
| <i>Aspect ratio</i>          | 4:3 wide TFT screen   |
| <i>Dot Resolution</i>        | 2400x600= 1,440,000 dots  |
| <i>Physical Resolution</i>   | 800x600   |
| <i>Supported Resolutions</i> | 640x480-1900x1200   |
| <i>Color configuration</i>   | RGB stripe  |
| <i>Power input</i>           | DC 12VDC  |
| <i>Power consumption</i>     | max. 45W  |
| <i>Video system</i>          | 1x Video input RCA (PAL/NTSC)<br>1x Video input S-Video<br>1x VGA input |

|                              |  |
|------------------------------|--|
| <i>Dimensions</i>            | Display Case : 310mm x 220mm x 20mm<br>Display : 246mm x 184.5mm   |
| <i>Video input signal</i>    | 1.0Vp-p, composite video   |
| <i>Brightness</i>            | 400 cd/m <sup>2</sup>  |
| <i>Contrast</i>              | 600:1  |
| <i>Vibration</i>             | IEC68-2-6  |
| <i>Operating Temperature</i> | -30° bis 85°C  |
| <i>Features</i>              | Full function OSD control (englisch)<br>VESA-mounting holes (75mm) |
| <i>Scope of supply</i>       | - 12.1" VGA Touchscreen TFI with Video-support                     |
|                              | - Mounting unit  |
|                              | - VGA-connector cable  |
|                              | - Power supply f. 110/230V Steckdose                               |
|                              | - Cigarette Lighter Adapter  |
|                              | - USB-connector cable  |
|                              | - Touchscreen Driver-CD  |
|                              | - Manual   |