



29.00 EUR

incl. 19% VAT, plus shipping

- Dual LAN!
- · Dual Output!
- 12V!
- 35W TDP Fanless!

Support: Specifications | Manual [EN]

NDiS 166 is specially designed to be mounted behind the large-size display device such as LCD TV or PDP. NDiS 166 supports dual display output by DVI, HDMI or VGA. The NDiS 166 operates on 2nd generation Intel® Core™ Processor Family with QM67 integrated graphics controller. NDiS 166 can smoothly playback dual Full HD video. NDiS 166 is ideal as advanced digital signage player for advertising, hospitality, brand promotion and digital menu board application

2nd generation Intel Core<sup>™</sup> processor family platform

Memory

- Intel integrated graphics engine
- Intel® AMT 7.0 Support
- Dual independent display
- Dual Gbe LAN

CPU 2nd generation Intel® Core™ rPGA socket type processor (up to

35W TDP)

Chipset Intel® QM67

Intel integrated graphics

2 x 240-pin DIMM sockets, Supports DDR3 1333/1066MHz

non-ECC,

un-buffered memory up to 16GB (Single socket max. 8GB)



2 x USB 2.0 2 x RS-232

Front I/O 2 x N3-232 1 x On/Off power switch

2 x LED for PW and HDD

1 x +12V DC-in

1 x VGA 1 x DVI-D 1 x HDMI

1 X HDD 0 0

**Rear I/O** 2 x USB 2.0

2 x RJ45 with LED for 10/100/1000 Mbps Ethernet

1 x SPDIF

1 x Line-out/1 x Line-in

2 x Antenna hole for Wi-Fi and TV tuner

Storage 1 x 2.5" SATA HDD bay

1 x Mini-PCle for optional wireless LAN module

1 x Mini-PCle for optional TV tupes module

1 x Mini-PCIe for optional TV tuner module

**Dimensions** 250mm (W) x 194mm (D) x 40mm (H)

(9.8" x 7.6" x 1.6") w/o mounting bracket

Construction Top cover made by aluminum for main heat exchange

Chassis made by steel in black

1 x External 80W AC/DC power adaptor

Power Supply Input: 100~240V AC

Output: +12V DC

Operating temperature : 0°C to 40°C

**Environment** Storage temperature : -20°C to 80°C

Humidity: 10 to 90% (non-condensing

Certification CE approval FCC Class A

Operating System Win7/Win8/XP/WES7/WE8S/WES2009/Linux