

٠ at usedouts 0

Now you can power every PC in 48V environments. 1000W power and P4 connector are giving you all possibilities ! The ATX connector has 24 pins.

Dimensions Weight Input Voltage Range Output Power maximum	200mm[W] × 150mm[L] × 86mm[H] 3.8 kgs 36 - 72V VDC	
	1000W	
Efficiency	75% typical @48V DC Full Load	
Output Power maximum (rails)	+3.3V : 23A +5.0V : 23A +12.0V : 80A	
Over Power Protection Peak power protected to 130%±10% of continuous rated power		
Over Voltage Protection	+3.3V@4.5V, +5V@6V, +12V@15.6V	
Short Circuit Protection	All output equipped with SCP (shutdown and latch off)	
MTBF	>90,000 hours @max. Load, 48V DC & 25°C ambient	
Safety Standards Operating Temperature	Meet IEC60950-1, EN60950-1	
	0°C ~ +50°C full load	

698.00 EUR incl. 19% VAT, plus shipping

STC-481000



Storage Temperature Humidity	/ -20°C~+80°C / 10%~90% RH. (Non condensing)
Cooling	Forced Air-cooling, 80x80x25 mm Fan x 1 pc
Connectors	1x ATX 24Pin
	2x 4pin HDD/DVD
	1x 4pin FDD
	8x Serial ATA
	2x 8pin Process EPS
	4x PCle (6+2)
Output Cable Length	610 mm