



1039.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Intel Core i3-1115G4E !
- 16x PoE !
- 4x RS232 !
- 2x 3,5" HDD !

- Intel® Core i3-1115G4E Processor
- 16-CH H.265/H.264 decoding ability & simultaneous playback
- 16-CH AI video analytics (7.1 TOPS)
- Equipped 0/8/16x 802.3 at/af PoE ports
- Support 2 x HDD RAID 0/1 storage

|                   |  |
|-------------------|--|
| CPU               | 11th Gen Tiger Lake-UP3 Intel® Core i3-1115G4E   |
| CHIPSET           | Intel® SoC Integrated  |
|                   | DDR4 3200 MHz  |
| SYSTEM MEMORY     | / 2 x 260-pin SO-DIMM  |
|                   | / Max. 64 GB (Non-ECC)   |
| GRAPHICS          | Intel® Iris Xe Graphics / Video Decoding (1080P,H264 / H.265): up to 64 channels / Video Recoding (1080P,H264 / H.265): up to 64 channels / Video Playback(1080P): up to 64 channels / Video Analytics / Deep Learning (1080P): 16 channels (7.1 TOPS) |
| DISPLAY INTERFACE | 2 x HDMI 1.4 (Up to 4K@30 Hz)  |
| STORAGE SLOT      | 2 x 3.5" internal HDD(RAID 0/1)  |
| ETHERNET          | Intel® I219-LM Giga LAN / Intel® I225-LM 2.5GbE LAN  |
| AUDIO             | Realtek® ALC888S   |
| I/O CHIPSET       | Nuvoton NCT6126D(eSPI)   |
| TPM               | Nuvoton NPCT750AABYX TPM2.0  |
| EXPANSION SLOT    | M.2 2280 / 2260 / 2242 M key (PCIe, SATA)  |
|                   | / Mini PCIe Full / Half size (PCIe / USB / SATA)   |
| INDICATOR         | Power Button / Alarm LED / Power LED / HDD LED   |
| FRONT I/O         | 2 x USB 2.0  |

---

|                        |   |
|------------------------|---|
| REAR I/O               | 2 x HDMI 1.4<br>/ 4 x USB 3.2 Gen 2<br>/ 1 x RS232<br>/ 1 x RS485<br>/ 2 x RJ-45<br>/ 1 x Line-out<br>/ 1 x Line-in |
| H/W MONITOR            | -   |
| WATCHDOG TIMER         | -   |
| POWER INPUT            | 100~240V AC-in  |
| POWER ADAPTER          | Built-in 250W Flex ATX PSU with AC Plug   |
| THERMAL DESIGN         | Fan   |
| MOUNTING               | Rackmount   |
| DIMENSIONS (W X D X H) | 19" 1U Chassis : 427 x 381 x 44.4 mm  |
| WEIGHT                 | 3.5 kg  |
| MATERIAL               | Bezel: Plastic / Chassis: Steel   |
| OPERATING TEMPERATURE  | 0 ~ 50°C (32 ~ 122°F)   |
| STORAGE TEMPERATURE    | -20 ~ 70°C (-4 ~ 158°F)   |
| OPERATING HUMIDITY     | 10% ~ 90% R/H (Non-condensing)  |
| VIBRATION RESISTANCE   | 5Hz~500Hz / 2Grms / 3Axis (Non-operating)   |
| SHOCK RESISTANCE       | 120G, 2ms Duration (Non-operating)  |
| CERTIFICATION          | CE / FCC Class B  |
| OS SUPPORT             | Windows® 10 64-bit / Linux (support by request)   |
| PACKAGE                | 1 x Quick Installation Guide / 1 x Embedded System / 1 x Screws kit / 1 x Rackmount kit                             |